

# **TECHNICAL DATASHEET**

## **BMA THINNER 2K**

Code: BMA-THI080

Color: Clear

## **PROPERTIES**

A high quality solvent blend formulated as a mixture of aliphatic hydrocarbons and used for diluting lacquers and two components systems. It is designed to reduce the gel strength, improve the flow of the products and as a cleaner for metal equipment and machinery used in the coating process.

### **RECOMMENDED USES**

BMA Thinner 2K could be used for:

- ✓ Lacquers
- ✓ Two components paints

## **PERFORMANCE BENEFITS**

- ✓ Ability to reduce gel strength
- ✓ Moderate evaporation
- ✓ Ability to reduce viscosity
- ✓ Good cleaning properties

## CHARACTERISTIC PHYSICO-CHEMICAL DATA

Tests	Norms	Results
Specific Gravity (g/cm³)	ASTM D1475	0.88

#### **AVAILABLE PACKAGING**

Gallons, Liters, Pails and Drums.



## **TECHNICAL DATASHEET**

### SHELF LIFE

BMA Thinner 2K must be stored in closed and undamaged containers in a well-ventilated area where the humidity does not exceed 75%, the temperature varies between 5°C and 35°C and away from any heat or freezing source.

Under these conditions the shelf life of BMA Thinner 2K will be 3 years. After this period, the product is subjected to re-inspection. Proper handling is essential to maintain good quality.

#### **HEALTH & SAFETY**

Before using this product please consult our Safety Data Sheet (SDS) for complete information on Hazards Identification, First-Aid and Fire-Fighting Measures, Accidental Release Measures, Handling and Storage, Exposure Control and Personal Protection, Stability and Reactivity, Toxicological Information, and Transport Information.

## **QUALITY ASSURANCE**

BMA Commercial & Industrial s.a.l is a holder of the ISO 9001:2015 and ISO 45001:2018 certificates, which guarantees that all operations are conducted in compliance with International Standards

#### TDS.100 - Edition #: 2

IMPORTANT: The statements, technical information and recommendations contained herein are believed to be accurate. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, BMA Commercial & Industrial s.a.l expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.