

## BMA THINNER LP

Code: BMA-THI160

Color: Clear

### PROPERTIES

A blend of aromatic and aliphatic hydrocarbons used as cleaner for equipment and tools before and after use.

### PERFORMANCE BENEFITS

- ✓ Good cleaning properties

### CHARACTERISTIC PHYSICO-CHEMICAL DATA

Tests	Norms	Results
Specific Gravity (g/cm <sup>3</sup> )	ASTM D1475	0.810
Consistency, at 25°C	ASTM D562	25s

<b>Acetate (5-35%)</b>
Ethyl Acetate
Methyl Acetate
Butyl Acetate
<b>Hydrocarbon (10-20%)</b>
Xylene
<b>Alcohol (20-60%)</b>
Methanol

## AVAILABLE PACKAGING

Gallons, Liters, Pails and Drums.

## SHELF LIFE

BMA Thinner LP must be stored in closed and undamaged containers in a well-ventilated area where the humidity does not exceed 75%, the temperature varies between 5 and 35°C away from a heating or freezing source.

Under these conditions the shelf life of BMA Thinner LP will be 3 years. After this period, the product is subjected to re-inspection. Proper handling is essential to maintain good quality.

## HEALTH & SAFETY

Before using this product please consult our Safety Data Sheet (SDS) for complete information on Hazards Identification, First-Aid and Fire-Fighting Measures, Accidental Release Measures, Handling and Storage, Exposure Control and Personal Protection, Stability and Reactivity, Toxicological Information, and Transport Information.

## QUALITY ASSURANCE

BMA Commercial & Industrial s.a.l is a holder of the ISO 9001:2015 and ISO 45001:2018 certificates, which guarantees that all operations are conducted in compliance with International Standards

TDS.233 - Edition #: 1

---

*IMPORTANT: The statements, technical information and recommendations contained herein are believed to be accurate. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, BMA Commercial & Industrial s.a.l expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.*